

WHAT IS CLAIMED IS:

1. A toner supply container detachably mountable to an image forming apparatus, comprising:

5 a main body, provided with an opening for permitting discharge of the toner, for accommodating the toner;

Sub Bk  
a sealing member for unsealably sealing the opening;

10 wherein the opening is unsealed by tearing a part of said sealing member,

wherein a pattern of welding with which said sealing member is welded on the main body of the container is inclined inwardly with respect to a tearing direction at a laterally outward end portion at a tearing starting side end portion.

20 2. A toner supply container according to Claim 1, wherein the welding pattern is inclined rectilinearly.

3. A toner supply container according to Claim 1, wherein said welding pattern is inclined with curvature.

Sub A1  
25 4. A toner supply container according to Claim 1, wherein the welding pattern is cut-away toward downstream with respect to the tearing direction, at a portion where the tearing starts in a welded portion.

BEST AVAILABLE COPY

5. A toner supply container according to Claim 1, wherein said sealing member has a seal portion welded to the main body of said container, and a sealing member pulling portion extended and folded back therefrom.

6. A toner supply container according to Claim 1, wherein said sealing member is provided with a tearing guide portion provided by laser irradiation.

7. A toner supply container according to Claim 1, wherein said sealing member has a cover film sealing the opening and a tear tape for tearing the cover film.

8. A process cartridge detachably mountable to an image forming apparatus, comprising:  
a developing portion, having a photosensitive member, for developing a latent image on the photosensitive member;

a toner accommodating portion for accommodating toner to said developing portion, said toner accommodating portion is provided with an opening for permitting discharging of the toner;

a sealing member for unsealably sealing the opening, wherein said sealing member has a seal portion welded to the main body of said container, and

BEST AVAILABLE COPY

Sub  
B2A

0004500  
0004500

Sub  
A2A

wherein the opening is unsealed by tearing a part of said sealing member,

10

15

20

25

12. A toner supply container according to Claim 8, wherein said sealing member is provided with a tearing guide portion provided by laser irradiation.

**BEST AVAILABLE COPY**

[illegible]

sub  
Aa  
conc.

13. A toner supply container according to Claim  
8, wherein said sealing member has a cover film  
sealing the opening and a tear tape for tearing the  
cover film.

5

10

15

20

25

2025-10-20 10:00:00

BEST AVAILABLE COPY